



EVOM™ AUTO

Accelerate Your Drug Discovery with Our **New** EVOM™ System With Both 24 and 96 HTS Multiwell Plate Capability



Automated TEER Measurement System

EVOM™ Auto with both 24 and 96 HTS multiwell plate capability is a high throughput screening (HTS) platform offering fast, non-invasive sample scanning by comparing electrical resistance measurements (transepithelial/transendothelial electrical resistance: TEER). TEER measurement experiments are simple to set up and less time consuming than more complex molecular studies. TEER measurement can be used as the primary scanning method to identify any physiological changes that can then be further evaluated by other methods. EVOM™ Auto can capture TEER measurements in 24 and 96 HTS multiwell plates from Corning, Millipore, or MatTek. The sample preparation time in these HTS plates is efficient, allowing for fast, multi-channel pipetting options.


Additionally, the EVOM™ Auto electrode disinfection capability during measurement minimizes sample cross-contamination. Its wireless device control offers the convenience of operating the instrument from a distance, and the small footprint of EVOM™ Auto enables you to use it inside a sterile cell culture hood or an incubator. The EVOM™ Auto provides a fast and efficient platform for early drug discovery, by narrowing down drug targets and drug concentrations through automated, non-invasive sample scanning.



EVOM™ AUTO EXPEDITES DRUG DEVELOPMENT AND LIFE SCIENCE RESEARCH BY ACCELERATING:

- *Hit Discovery Process*
- *Hit To Lead*
- *Target Screening, Identification and Validation*
- *Formulation Optimization & Improving Bioavailability*
- *Assay Development*
- *Safety Assessment: Toxicity*
- *Quality Control of 2-D and 3-D*
- *In Vitro Tissue Models in Drug Discovery*

APPLICATIONS




Epithelial Barrier Function



Drug Absorption Studies



Tissue Engineering/Cell Culture



Disease Modeling



QC in Cell-Based Assays & Cell Therapies



Manufacturing Quality Control

SPECIFICATIONS

Autosampler Dimensions (WxDxH)	40 x 25 x 21 cm
Autosampler Weight	7 kg
Compatibility	Corning, Millipore, and MatTek 96-well HTS Plates with 96 -well electrode array (EVA-EL-03-01) Corning 24-well HTS plates with 24C electrode array (EVA-EL-03-02) Millipore 24-well HTS plates with 24M electrode array (EVA-EL-03-03)
Rinse Stations	3
Electrode Array for 96 HTS Plate	Array of 8 pair of (1.2mm Φ) electrodes
Electrode Array for 24 HTS Plate	Array of 4 pair of (1.2mm Φ) electrodes
Minimum Sample Reading Time	1 Second

Control Device to Run Software	Tablet, Laptop, Desktop with Wi-Fi adapter
Output Data	CSV/Microsoft® Excel
Resistance Range	10KΩ, 50KΩ, 100KΩ
21 CFR Part 11 Option	Yes, when used with either EVA-GXP-01-01 or EVA-GXP-01-02
CE Certified	Yes
UL Certified	Yes

SYSTEM (CONFIGURATION) OPTIONS

- EVA-MT-03-01 for 96-well HTS (Corning, Millipore, and MatTek)
- EVA-MT-03-02 for Corning 24-well HTS
- EVA-MT-03-03 for Millipore 24-well HTS

NOTE: The system configurations can be used for any of the listed plate types (24 or 96) by easily switching the electrode arrays and plate adapters. The electrode array heads and plate adapter switch mechanism enables you to analyze samples in different plate types.



SAVE TIME BY AUTOMATING YOUR PROCESS AND MOVE THROUGH A PLATE QUICKLY



FLEXIBILITY TO MANAGE YOUR DATA



MINIMIZE HUMAN ERRORS



HARDWARE SETUP IS EASY AND REQUIRES NO CONFIGURATION



MINIMIZE PROBE DAMAGE AND AVOIDS COSTLY REPAIRS



WITH COMPLETE CONTROL OF THE SYSTEM, YOU CAN FINE TUNE THE PROGRAMMING AS DESIRED



EASY-TO-NAVIGATE SYSTEM SAVES TIME WHEN CONFIGURING SEQUENCES

Part Numbers

EVOM™ Auto System

EVA-MT-03-01	EVOM™ Auto for TEER Measurement in 96 HTS Plate
EVA-MT-03-02	EVOM™ Auto for TEER Measurement in 24C HTS Plate
EVA-MT-03-03	EVOM™ Auto for TEER Measurement in 24M HTS Plate

Accessories & Options

EVA-AC-03-02-10	Disposable Rinse Station Inserts (Sterile), pkg of 10
EVA-AC-03-02-25	Disposable Rinse Station Inserts (Sterile), pkg of 25
EVA-EL-03-01	EVOM™ Auto 96 HTS Electrode Array for TEER
EVA-EL-03-02	EVOM™ Auto 24C HTS Electrode Array for TEER
EVA-EL-03-03	EVOM™ Auto 24M HTS Electrode Array for TEER
EVA-MT-03-INS	EVOM™ Auto On-Site Installation & Training
EVA-MT-03-IOQ	IQ/OQ Documentation for EVOM™ Auto Instrument
EVA-GXP-01-01	GxP Compliance Module Option A (Store all files), Powered by TotalLab
EVA-GXP-01-02	GxP Compliance Module Option B (Store only data), Powered by TotalLab,
EVA-GXP-01-03	EVOM™ Auto GxP Yearly Renewal Powered by TotalLab
EVA-GXP-01-04-UPGR-S	EVOM™ Auto Upgrade to GxP Module, Option A
EVA-GXP-01-04-UPGR-R	EVOM™ Auto Upgrade to GxP Module, Option B
EVA-GXP-01-05-IOQ-V	Virtual IQ/OQ for GxP Module by TotalLab
EVA-GXP-01-05-IOQ-O	Onsite IQ/OQ for GxP Module by TotalLab

Warranty & Services

EVA-MT-03-EX1	EVOM™ Auto 1 Year Premium Warranty
EVA-MT-03-EX2	EVOM™ Auto 2 Year Premium Warranty
EVA-MT-03-CAL	EVOM™ Auto Annual Inspection and Calibration

System Includes

EVOM™ Auto TEER Measurement System (EVA-MT-03-xx) includes the autosampler, an electrode array with accessories (for 96 or 24 HTS multiwell plates), an interface unit and its cable, an iPad control tablet with software, and a power cord.

Electrode Array

- Specially designed electrode array fits precisely in the HTS plates from Corning, Millipore, and MatTek, ensuring consistent placement
- Perform resistance measurements directly in the HTS plates, common or divided, reducing the possibility of contamination and mechanical damage to your cultured cells
- Array of multiple electrode pairs enhances the throughput by saving time to read the samples due to shorter sampling time and shorter time requirement for disinfecting electrodes in between measurements
- Measures a whole column of wells each time the electrode array moves once

96 Well Array


- Measures a Column of 8 Wells Sequentially
- Array of 8 pair of (1.2mm Φ) electrodes



EVA-EL-03-01

24 Well Array

- Measures a Column of 4 Wells Sequentially
- Array of 4 pair of (1.2mm Φ) electrodes



EVA-EL-03-03

Sterile Disposable Rinse Station Inserts

- Packages of 10 or 25
- Individually sterile
- For convenient and effective electrode disinfection
- Use a fresh sterile one after each sample plate reading or before switching to different set of sample plates



EVA-AC-03-02-XX

EVOM™ GxP Compliance Module

- EVOM™ GxP Compliance Module powered by TotalLab
- Able to meet regulations related to electronic records and signatures of US: 21 CFR Part 11, subparts B and C and EU: Annex 11
- EVOM™ GxP software can be adopted to address GLP/GMP requirements

